

- True deep cycle AGM technology-GREEN SOLUTION
- Over 99.99% virgin lead for grid plate and active material
- Heavy duty grid/paste design for deep cycle application
- Maintenance free, non-spillable, valve-regulated
- Double separator configuration: long cycle life & high energy density and super anti-vibration design
- Low self-discharge for longer shelf life



■ ELECTRICAL SPECIFICATIONS

Voltage (V)	Capacity (AH)					Reserve Capacity (Min)		
	100HR	20HR	10HR	5HR	3HR	@25A	@56A	@75A
6	385	350	332	305	285	820	/	240

■ PHYSICAL SPECIFICATIONS


Model	Dimensions (mm/inches)				Weight (kg/lbs)	Terminal Type (Standard)	Case Material
	Length	Width	Height	Total Height			
PC6-350-902	295 (11.61)	180 (7.09)	346 (13.62)	368 (14.49)	48.0 (105.8)	DT-3/8	PP

■ OPERATING TEMPERATURE RANGE

Discharge	Charge	Storage
-15°C ~ 50°C (5°F ~ 122°F)	0°C ~ 40°C (32°F ~ 104°F)	-15°C ~ 40°C (5°F ~ 104°F)


■ APPLICATIONS

- | | | |
|-----------------------------------|-----------------|-----------------|
| Energy Storage / Renewable Energy | Boats and Ships | Solar & Wind |
| Recreational Vehicles | Generators | Golf Carts |
| Fort Lift Trucks | Motive Power | Traffic Signals |
| Uninterruptable Power Supplies | | |




Deep Cycle SLA Battery

■ Dimensions




Note: D:Positive 19.5⁰_{-0.3}, D:Negative 17.9⁰_{-0.3}; Terminal Torque Values in-lb(Nm) :176-203(20-23)

■ Charging Profile




■ Relationship of OCV & State of Charge

25°C | 77°F



■ Cycle Life in Relation to Depth of Discharge



■ Self-Discharge Characteristic

