











	PRODUCT NAME	VOLTAGE (V)	AMP HOUR (AH)	ENERGY (WH)	MAX CONTINUOUS DISCHARGE CURRENT (A)	DISCHARGE CUTOFF (V)	CHARGE VOLTAGE (V)	MAX CHARGE CURRENT (A)	INTERNAL RESISTANCE (MΩ)	OPERATING TEMP (°C)	LENGTH (MM)	WIDTH (MM)	HEIGHT (MM)	APPROX. WEIGHT (KG)	TERMINAL TYPE
	PCLFP7.5-12.8F2	12.8	7.5	96	7.5	10	14.6	7.5	<60	Charge: 0 ~ 45 Discharge: -20 ~ 60	151 (+/-1)	65 (+/-1)	99 (+/-1)	1.1	F2
	PCLFP10-12.8F2	12.8	10	128	10	10	14.6	10	<60	Charge: 0 ~ 45 Discharge: -20 ~ 60	151 (+/-1)	98 (+/-1)	101 (+/-1)	1.6	F2
	PCLFP20-12.8M6	12.8	20	256	20	10	14.6	15	<50	Charge: 0 ~ 45 Discharge: -20 ~ 60	181 (+/-1.5)	77 (+/-1.5)	167 (+/-1.5)	2.75	M6
	PCLFP30-12.8M6	12.8	30	384	30	10	14.6	15	<50	Charge: 0 ~ 45 Discharge: -20 ~ 60	195 (+/-2)	130 (+/-2)	17 (+/-2)	4.7	M6
	PCLFP40-12.8M6	12.8	40	512	40	10	14.6	20	<20	Charge: 0 ~ 45 Discharge: -20 ~ 60	197 (+/-2)	165 (+/-2)	170 (+/-2)	5.75	M6
	PCLFP55-12.8M6	12.8	55	704	55	10	14.6	20	<20	Charge: 0 ~ 45 Discharge: -20 ~ 60	229 (+/-2)	138 (+/-2)	212 (+/-2)	8.2	M6
	PCLFP60-12.8M6	12.8	60	768	60	10	14.6	30	<20	Charge: 0 ~ 45 Discharge: -20 ~ 60	259 (+/-2)	168 (+/-2)	214 (+/-2)	9	M6
	PCLFP100-12.8M6	12.8	100	1280	100	10	14.6	50	<20	Charge: 0 ~ 45 Discharge: -20 ~ 60	342 (+/-2)	173 (+/-2)	220 (+/-2)	13.6	M6
	PCIFR18650-1500	3.2	1.5	4.8	1.5	2.5	3.65	1.5	<60	Charge: 0 ~ 45 Discharge: -20 ~ 60	Dia: 18.2 (+/-0.1)	NA	65.5 (+/-0.2)	45g	NA
	PCIFR26650-3300	3.2	3.3	10.56	9.0	2.0	3.65	3.3	<20	Charge: 0 ~ 45 Discharge: -20 ~ 60	Dia: 26.1 (+/-0.2)	NA	65.5 (+/-0.2)	88g	NA