

**Specifications**

<b>Item Description</b>	Smart CC/CV	12.8V / 5A LiFePO <sub>4</sub> Battery Charger w/ 4ft alligator clips cable
	CAUTION: Designed for charging 12.8V LiFePO <sub>4</sub> batteries only	
<b>Input</b>	Rating Input Voltage (VAC)	100 ~ 240 (47 - 63Hz)
	Input Voltage Range (VAC)	90 ~ 264 (47 - 63Hz)
	Max Input Current (A)	2
<b>Output</b>	Output Voltage (VDC)	14.4 ± 0.2V
	Output Current (mA)	5000 ± 5%
	Safety & EMC	IEC60601-1 & EN55014 / EN61000
	Max Output Power (W)	72
	LED Color	Green ON: Charged / Standby Red ON: Charging Red Flashing: Fault LED Off: No AC Power
	Short Circuit Protection	Present, Self Recovery
	Reverse Polarity Protection	Present, Self Recovery
<b>Environmental</b>	Operating Temperature (°C)	0 ~ +40
	Operating Humidity (%)	20 ~ 85
	Storage Temperature (°C)	-40 ~ +70
	Storage Humidity (%)	10 ~ 95
	Maximum Altitude (m)	3000
<b>Mechanical</b>	Weight (approx.) (kg)	0.36
	Size (case only) L x W x H (mm)	141 x 60 x 34
	Input Plug	2-prong USA
	Output Cable Length (ft)	4
	Output Connector	Black Alligator - Negative Red Alligator - Positive

