

- True deep cycle AGM technology-GREEN SOLUTION
- Over 99.99% virgin lead for grid plate and active material
- Heavy duty grid/paste design for deep cycle application
- Maintenance free, non-spillable, valve-regulated
- Double separator configuration: long cycle life & high energy density and super anti-vibration design
- Low self-discharge for longer shelf life



■ ELECTRICAL SPECIFICATIONS

Voltage (V)	Capacity (AH)					Reserve Capacity (Min)		
	100HR	20HR	10HR	5HR	3HR	@25A	@56A	@75A
12	130	118	113	107	98	239	95	65

■ PHYSICAL SPECIFICATIONS

Model	Dimensions (mm/inches)				Weight (kg/lbs)	Terminal Type (Standard)	Case Material
	Length	Width	Height	Total Height			
PC12-118-G31-DT	330 (12.99)	173 (6.81)	212 (8.35)	237 (9.33)	31.7 (69.9)	DT-5/16	ABS

■ OPERATING TEMPERATURE RANGE

Discharge	Charge	Storage
-20°C ~ 60°C (-4°F ~ 140°F)	0°C ~ 50°C (32°F ~ 122°F)	-20°C ~ 60°C (-4°F ~ 140°F)




■ APPLICATIONS


Energy Storage / Renewable Energy	Boats and Ships	Solar & Wind
Recreational Vehicles	Generators	Golf Carts
Fort Lift Trucks	Motive Power	Traffic Signals
Uninterruptable Power Supplies		

Deep Cycle SLA Battery

■ Dimensions




DT-5/16 Terminal



D: Positive 19.5 +0/-0.3, D: Negative 17.9 +0/-0.3


Terminal Torque Values in-lb (NM): 176-203 (20-23)

■ Charging Profile




■ Relationship of OCV & State of Charge

25°C | 77°F



■ Cycle Life in Relation to Depth of Discharge



■ Self-Discharge Characteristic

