



**Non-Rechargeable Zinc Carbon**

**■ Specifications**

<b>Type Designation</b>	IEC/JIS 6F22 Common: 9V
<b>Chemical System</b>	Zn/ZnCl <sub>2</sub> -NH <sub>4</sub> Cl-H <sub>2</sub> O/MnO <sub>2</sub>
<b>Nominal Voltage</b>	9.0V
<b>Nominal Capacity</b>	Approx. 350mAh 620Ω 2h/d, 20°C 5.4V cut-off voltage
<b>Weight</b>	Approx. 35g
<b>Operating Temperature</b>	0°C ~ 45°C
<b>Recommended Storage Temp.</b>	Not to exceed 30°C
This product complies with EU's battery directive (2016/66/EC). Packaging materials comply with EU's directive on packaging materials and waste (94/62/EC)	



/	min	max
H	46.5	48.5
S	-	46.4
F	12.45	12.95
L	24.5	26.5
W	15.5	17.5

**■ Open Circuit Voltage and Closed Circuit Voltage**

	Initial		Stored 1 Year	
	Min.	Norm.	Min.	Norm.
<b>OCV (V)</b>	9.8	10.2	9.6	9.7
<b>180Ω 0.3sec CCV (V)</b>	8.8	9.1	8.6	8.8

**■ Load Performance**

Load	Test Mode	End Voltage	Applications	Unit	Initial	Stored 1 Year
<b>180Ω</b>	24h/d	4.8V	Reference	m	210	200
<b>270Ω</b>	1h/d	5.4V	Microphone	h	10	9
<b>620Ω</b>	2h/d	5.4V		h	29	27.5
<b>10KΩ 24h/d 620Ω 1s/h</b>		7.5V		d	8.0	7.2

**■ Expiration Date Marking**

Unless otherwise specified, each battery will carry a DOM code followed by month and year. Shelf life for Zinc Carbon batteries is 36months from DOM.